

# Nylon Premier Lawn

A 1.5 inch pile, nylon monofilament with thatch construction. Designed specifically for landscape application to enhance recovery.

Recommended Use: Moderate to Heavy Traffic  
Main Application: Landscape  
Colors: Jade Green/Spring Green

## LEAD FREE PRODUCTS:

- All of our products undergo rigorous stringent testing to ensure safety and non-toxicity.
- Our products contain no detectable traces of lead or other RCRA hazardous waste heavy metals.



**CALL TODAY! 877.643.8006**

## Main Advantage

- **100% Nylon** - Delivers superior performance, stronger than polyethylene
- **A 1.5 inch blade height** helps to achieve a natural appearance
- **Uniquely superior tuft bind of 16.5 lbs** creates greater seam strength and durability
- **Ideal for heavy traffic landscape or play areas**, as well as roof deck or putting green fringe applications
- **UV stabilized | Not water soluble**
- **Heat and frost resistant. No harmful environmental effects**
- **Non-flammable, anti-acid yarn resistant to chemical attack with ASTM E108 Class A fire rating**

| Property                              | Description         | ASTM       |
|---------------------------------------|---------------------|------------|
| Yarn Type:                            | Nylon               |            |
| Yarn Color:                           | Jade   Spring Green |            |
| Thatch Color:                         | Sandstone   Olive   |            |
| Total Face Weight:                    | 65 oz/sy            |            |
| Pile Height:                          | 92 oz/sy            |            |
| Yarn Denier:                          | 1-1/2"              |            |
| Yarn Type:                            | 8800/8-1100         |            |
| Backing System:                       | Black Urethane      |            |
| Width:                                | 15 feet             |            |
| Turf Bind:                            | 16.5lbs             | ASTM D1335 |
| Flammability: (Pill Test)             | Pass                | ASTM D2859 |
| Flammability: (Critical Radiant Flux) | Pass                | ASTM E648  |
| Lead Levels:                          | Compliant           | ASTM F1765 |
| Grab Tear Strength:                   | Pass                | ASTM 5034  |
| Impact Attenuation:                   | Pass - 11'          | ASTM F1292 |
| ADA Wheelchair Accessibility:         | Compliant           | ASTM F1951 |
| Water Permeability:                   | 442.68 in/hr        | ASTM F1551 |
| Fire Test for Roof Decks:             | Class A             | ASTM E108  |
| Smoke Density:                        | Class C             | ASTM E84   |
| Manufacturers Warranty:               | 15 Year Warranty    |            |



EXCLUSIVELY  
DISTRIBUTED  
BY SGW

